# INTERNATIONAL EUROVAULT

Feature-packed Burglary and Fire-Resistant Safe



Using high density aggregate compound

• 3-Way Boltwork

With massive 11/4" chrome-plated bolts with autolock bolt detent

Digital Lock (optional)

All safes come standard with U.L. Listed Group IIM combination lock with satin finish dial, dial ring & handle.

Door and Body

2" thick barrier walls and door slab

Shelves -

Adjustable shelves are standard

• High Tensile Strength Hardplate

Drill resistant stainless steel polished fascia panel

Key Lock

High security key lock is standard most models

• 1-Hour Fire Protection

Rated at 1500° incorporating expandable fire gasket surrounding door jamb















CANNABIS





















## **INTERNATIONAL EUROVAULT**


### **Specifications**












Model	Interior H x W x D (in)	Exterior H x W x D (in)	Weight (lbs)	Capacity (cu ft)	Shelves
EV-1713	17 x 13 x 13	21 x 17 x 19½	420	1.6	1
EV-1717	17 x 17 x 17	21 x 21 x 23½	550	2.8	1
EV-2417	24 x 17 x 17	28 x 21 x 23½	665	4.2	2
EV-3417	34 x 17 x 17	38 x 21 x 23½	900	5.6	2
EV-4517	45 x 17 x 17	49 x 21 x 23½	1,124	7.5	3

#### **Door Swing Dimensions**


Model	Dimensions (in)			
Model	A	В	C	
EV-1713	13	31	28	
EV-1717	17	421/2	381/4	
EV-2417	17	421/2	381/4	
EV-3417	17	421/2	381/4	
EV-4517	17	421/2	381/4	

Add 2" to exterior depth for hinge projection. Add 2" to exterior depth for handle projection.

#### **Door Swing Projections**



## Security Installation Platform



Each Eurovault Series Safe comes equipped with the revolutionary Security Installation Platform (SIP), an exclusive innovation that ensures accurate and secure installation.

#### **Distributed By:**

FIRE RESISTANT SAFE: 1-HOUR RATING
Safe was tested by an independent
laboratory in a furnace at temperatures up
to 1500°F for a period of 1 hour. Interior
temperatures did not exceed 350°F.